

GENERAL

ALIAVA The AVF250 Series flowmeter is commonly used in location that required on-site analog flow indication.

The meter accurately measures small volumes / wide ranges of liquids, gases and steam.

FEATURES

- ❑ 5 Digit Flowrate & 7 Digit Totalizer
- ❑ Integrated temperature and pressure compensation
- ❑ Local indication without auxiliary power
- ❑ 4-20 mA and scale pulse output
- ❑ Low pressure loss in gas and steam application
- ❑ Damper for Gas / Steam application
- ❑ Consistent overall length
- ❑ Heating jacket design
- ❑ Intrinsically safe & explosion proof for hazardous area

STANDARD SPECIFICATION

- Size : 15,20,25,40,50,65,80,100,125,150,200 mm
- Measuring Range : Liquid _1~200000 L/hr
: Gas _0.03~3000 m³/hr
- Turndown Ratio : 10:1 (20:1 Optional)
- Accuracy : +/-1.6% (Standard)
: +/-1.0% (Optional)
- Repeatability : +/-0.5% FS
- Material
 - Tube & Float : Stainless Steel 304
 - : Stainless Steel 316
 - : Stainless Steel 316L
 - : Stainless Steel + PTFE Liner
- Standard Pressure : 40 kgf/cm² (15-50 mm)
: 16 kgf/cm² (65-200 mm)
- Temperature : -25~200 °C (Standard)
: -25~100 °C (LCD Display)
: 0~80 °C (PTFE Liner)
: -80~400 °C (Optional)
- Flange Type : JIS 10K / JIS 20K / JIS 40K
ANSI 150# / ANSI 300# / ANSI 600#
DIN PN10 / PN16 / PN25 / PN40
- Fluid Viscosity : 300 cP Max.
- Communication : RS485 (MODBUS Protocol)
: HART signal (Compatible)



With LCD Display



Local Indication



T & P Compensation



Explosion Proof

- Local Display : Mechanical Indicator (Standard)
Digit Display : 5 Digit Flowrate
: 7 Digit Totalizer
- Current Output : 4-20 mA (2-Wire)
Load : Max. 600 Ω
- Pulse Output : Open collector (Scaled pulse)
Rating : 3-30 VDC, 100 mA Max.
- Data Storage : Operation parameters and totalizer figures are stored by EEPROM for more than 10 years
- Limit Switches : 2-Wire NAMUR (For Exia / Exd)
3-Wire transistor
- Keypad : 3 Internal keys for programming and display control
- Ambient Temperature : -25~60 °C
- Protection Class : IP65
: Intrinsically Safe, Eex ia IIC T5
: Explosion Proof, Ex d IIC T6
- Housing Material : Aluminum Alloy
- Cable Entry : Standard: M20 Option: 1/2" NPTF
- Pressure Loss : 0.07-0.7 kgf/cm²
- Power Supply : 12-32 VDC
: Ni-MH Battery (3 years working hours)
- Option : Temp. & Pressure compensation



ALIA TECHNOLOGY LLC

633 W. 5th Street, 26th Floor, Los Angeles, CA 90071, USA
TEL : + 1 - 213 - 533 - 4139 FAX : + 1 - 213 - 223 - 2317



URL : www.alia-inc.com
E-mail : alia@alia-inc.com
AVF250V1.2.3.r6.A4.en

FLOW RANGE

Size				Float No.	S.S. 304 / 316 / 316L	S. S. + PTFE	S.S. 304 / 316 / 316L
					Water, 20 °C		Air, 0 °C, 1 ATM
					L/hr	L/hr	m ³ /hr
15 mm	1/2"	20 mm	3/4"	F15.0	1.0 - 10		0.03 - 0.3
				F15.1	1.6 - 16		0.07 - 0.7
				F15.2	2.5 - 25	1.6 - 16	0.11 - 1.1
				F15.3	4.0 - 40	2.5 - 25	0.18 - 1.8
				F15.4	6.3 - 63	4.0 - 40	0.28 - 2.8
				F15.5	10 - 100	6.3 - 63	0.4 - 4.0
				F15.6	16 - 160	10 - 100	0.7 - 7
				F15.7	25 - 250	16 - 160	1.0 - 10
				F15.8	40 - 400	25 - 250	1.6 - 16
				F15.9	63 - 630	40 - 400	3.0 - 30
25 mm	1"	40 mm	1-1/2"	F25.0	63 - 630		
				F25.1	100 - 1,000	63 - 630	3.0 - 30
				F25.2	160 - 1,600	100 - 1,000	4.5 - 45
				F25.3	200 - 2,000		
				F25.4	250 - 2,500	160 - 1,600	7.0 - 70
				F25.5	320 - 3,200		
				F25.6	400 - 4,000	200 - 2,000	12 - 120
				F25.7	500 - 5,000	250 - 2,500	
F25.8	630 - 6,300	320 - 3,200	18 - 180				
50 mm	2"	65 mm	2-1/2"	F50.0	500 - 5,000		
				F50.1	630 - 6,300	400 - 4,000	18 - 180
				F50.2	1,000 - 10,000	630 - 6,300	25 - 250
				F50.3	1,600 - 16,000	1,000 - 10,000	40 - 400
				F50.4	2,000 - 20,000	1,600 - 16,000	
80 mm	3"			F50.5	2,500 - 25,000		63 - 630
				F80.0	1,600 - 16,000		
				F80.1	2,000 - 20,000		
				F80.2	2,500 - 25,000	1,600 - 16,000	70 - 700
100 mm	4"			F80.3	4,000 - 40,000	2,500 - 25,000	120 - 1,200
				F80.4	6,300 - 63,000		180 - 1,800
				F100.0	4,000 - 40,000	2,500 - 25,000	
				F100.1	6,300 - 63,000	4,000 - 40,000	180 - 1,800
150 mm	6"	125 mm	5"	F100.2	8,000 - 80,000		
				F100.3	10,000 - 100,000		300 - 3,000
				F150.0	8,000 - 80,000		
200 mm	8"			F150.1	10,000 - 100,000		300 - 3,000
				F150.2	15,000 - 150,000		
				F200.0	15,000 - 150,000		
				F200.1	20,000 - 200,000		

DIMENSIONS

BT (Bottom-Top)			
Size mm	A mm	Weight kg	ΔP mbar
15	133	3.7	140
25	121	5.6	190
50	106	9.7	230
80	93	15	330
100	84	17	420
150	65	34	600
200	29	49	700

BR (Bottom-Top Side)					
Size mm	H mm	L mm	A mm	weight kg	ΔP mbar
15 mm	330	250	120	7.0	180
25 mm	340	250	120	8.0	220
50 mm	560	250	120	15	280
80 mm	595	250	150	25	350
100 mm	600	250	150	29	450
150 mm	690	300	180	53	580
200 mm	780	350	200	61	700

LR / RL (Horizontal)				
Size mm	H mm	L mm	weight kg	ΔP mbar
15	355	250	7.5	300
25	370	250	9	350
50	643	250	18	400
80	690	400	29	450
100	720	400	35	500
150	793	500	60	630
200	970	550	73	850

RR (Bottom Side-Top Side)					
Size mm	H mm	L mm	A mm	weight kg	ΔP mbar
15	380	250	120	7.2	200
25	400	250	120	8.7	280
50	643	250	120	16.6	360
80	675	250	150	28.2	450
100	700	250	150	33.5	580
150	832	300	180	58	630
200	950	350	200	68	700

MODEL SELECTION GUIDE

AVF250 Series									
Example: AVF250-050-S6ABT-B-IT-D									
AVF250-	XXX	-XX	X	XX	-X	-XX	-X	Description	
Size	015-200							15-200 mm (1/2"-8")	
Material	-S4							Stainless Steel 304	
	-S6							Stainless Steel 316	
	-SL							Stainless Steel 316L	
	-4P							Stainless Steel 304 + PTFE Liner	
	-6P							Stainless Steel 316 + PTFE Liner	
Process Connection	1							PN10	
	2							PN16	
	3							PN25	
	4							PN40	
	A							ANSI 150#	
	B							ANSI 300#	
	C							ANSI 600#	
	J							JIS 10K	
	K							JIS 20K	
	L							JIS 40K	
Z							Others		
Flow Direction	BT							Bottom-Top	
	BR							Bottom-Top Side	
	RR							Bottom Side-Top Side	
	LR							Left-Right (Horizontal)	
	RL							Right-Left (Horizontal)	
Function	-A							Local Indication	
	-B							Local Indication + Rate 5 digit / Totalizer 7 digit + 4-20 mA	
	-C							Local Indication + Rate 5 digit / Totalizer 7 digit (Battery Power)	
	-F							Local Indication + One point Alarm (2-Wire NAMUR or 3-Wire transistor)	
	-G							Local Indication + Two point Alarm (2-Wire NAMUR or 3-Wire transistor)	
Protection Class	-NN							IP65	
	-IT							Intrinsically Safe, Eex ia IIC T5	
	-EX							Explosion Proof, Ex d IIC T6	
Option	-N							None	
	-C1							RS485 (MODBUS Protocol)	
	-C2							HART Signal (Compatible)	
	-D							Damper (For Steam & Gas Application)	
	-H							Heating Jacket	
	-P1							Pulse Output * 1 (With Function B Only)	
	-P2							Alarm Output * 2 (With Function B Only)	
	-R2							Relay Output * 2 (1A@30 VDC, 0.5A@125 VAC) (With Function B Only)	
	-T							Max. Temp. higher than 200 °C (100 °C for LCD Display)	
	-PT							Cable Entry 1/2" NPTF	
	-TC							Temperature compensation *Note	
	-PC							Pressure compensation *Note	
	-CM							Temp. and Pressure compensation *Note	

Note: With Size 15-100, Material S4/S6/SL, Flow Direction Bottom-Top, Function B Only.